


(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
21 August 2003 (21.08.2003)

PCT

(10) International Publication Number  
**WO 03/069815 A1**

- (51) International Patent Classification<sup>7</sup>: **H04B 17/00, 7/005**
- (21) International Application Number: **PCT/EP02/00996**
- (22) International Filing Date: 30 January 2002 (30.01.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (71) Applicant (for all designated States except US): **TELEFONAKTIEBOLAGET L M ERICSSON (PUBL)** [SE/SE]; 30, Telefonvagen, SE-12625 Stockholm (SE).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **ASCHERMANN, Benedikt** [DE/DE]; Illexweg 1a, 42111 Wuppertal (DE).
- (74) Agent: **VAN DER AREND, A., G., A.**; Exter Polak & Charlois B.V., P.O. Box 3241, NL-2280 GE Rijswijk (NL).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND SYSTEM FOR TRANSMISSION OF CARRIER SIGNALS BETWEEN FIRST AND SECOND ANTENNA NETWORKS

(57) Abstract: Method and system for transmission of carrier signals, each of which occupy a different radio-frequency band, between first and second antenna networks (14, 15), each comprising a plurality of distributed antenna's (6), with the first antenna network (14) being coupled to a main coupling device (3) and to an intermediate coupling device (21), the second antenna network (15) being coupled to the intermediate coupling device (21), and with the coupling devices (3, 21) being coupled to one or more peripheral devices (8, 22), wherein the intermediate coupling device (21) is controlled to have a carrier signal frequency band of the second antenna network (15) occupied by a carrier signal which is exchanged with a peripheral device (8) which is coupled to the main coupling device (3) or with a further peripheral device (22) which is coupled to the intermediate coupling device (21).

WO 03/069815 A1